sterilwave

Medical Waste.
Treated. On site.

Sterilwave 900

FOR

HOSPITALS
CLINICS
LABORATORIES

150 kg/h | 1500 L/h



Sterilwave 900 combines rotative blades shredding and microwave technology in one single vessel to treat infectious healthcare waste on site.

Compact. No transport. No pressure.
No liquid effluent. No incineration.

sterilwave.com

35 min	Up to 8 log 10	Up to 85 %	Up to 25 %
AUTOMATIC CYCLE	MICROBIAL INACTIVATION	VOLUME REDUCTION	WEIGHT REDUCTION

THE PROCESS

30 minutes.
1 single vessel.

20° C

LOAD
Infectious waste

SHRED
with rotating blades

TREAT
with microwaves

DISCHARGE
safe waste

From infectious
to municipal waste.

110° C

BEFORE



AFTER



Sterilwave 900

150 kg/h 1500 L/h

Based on 0.1 kg/L. May vary with waste type.
Excludes handling between cycles.

Treatment chamber volume	900 L
Typical cycle time	35 minutes
Dimensions, main unit (L × W × H)	4.8 × 3.7 × 2.45 m
Approximate weight	3000 kg
Power supply	400 V / 3-phase / 50 Hz / 150 A
Typical electrical consumption per cycle	~22.7 kWh
Recommended floor surface	40 m²
Recommended ceiling height	4 m
Loading method	Automatic
Electronic weighing	Included
Technology	Shredding by rotative blades and heating by microwaves
Volume reduction	Up to 85%
Weight reduction	Up to 25%
Final waste	Unrecognisable, inert, dry and stable



THE STERILWAVE RANGE



10 kg/h	20 kg/h	50 kg/h	88 kg/h	150 kg/h
Sterilwave 50	Sterilwave 100	Sterilwave 250	Sterilwave 440	Sterilwave 900

Non-contractual document and pictures. Specifications subject to change without notice. Sterilwave 2026